

FO 103-S

Fiber Optic Stripper Line

- For stripping 250 micron buffer coating from 125 micron optical fiber
- Precision diameter hole & V-opening in blade allow for accurate buffer coating removal
- Pivot pin, spring and precision handles enhance tool functionality and durability
- Factory set, requires no adjustment
- Prevents scratching or nicking of optical fiber
- All cutting surfaces are precision formed, hardened, tempered and ground assuring precise buffer removal
- Made in the U.S.A.
- Length: 5.375 in (136.53 mm)
- Weight: 2.5 oz (71 g)



FO 103-S – Custom Applications

- The same quality FO 103-S construction is available in a variety of stripping fiber diameters
- Currently available models shown below
- If your application is not listed here, please Contact Customer Service



Part Number	Model	Finished Cladding Diameter	
		(Microns)	(Inches)
80355	FO 103-S	125 μm	.005 in
80355-1	FO 103-S-100	80-100 μm	.003-.004 in
80355-15	FO103-S-140	140 μm	.0055 in
80355-2	FO 103-S-150	150 μm	.006 in
80355-3	FO 103-S-162	162 μm	.0065 in
80355-4	FO 103-S-175	175 μm	.007 in
80355-5	FO 103-S-187.5	187.5 μm	.0075 in
80355-10	FO 103-S-200	200 μm	.008 in
80355-12	FO 103-S-225	225 μm	.009 in
80355-6	FO 103-S-250	250 μm	.010 in
80355-7	FO 103-S-280	275-280 μm	.011 in
80355-8	FO 103-S-300	300 μm	.012 in
80355-16	FO-103-S-400	400 μm	.016 in
80355-9	FO 103-S-525	525 μm	.021 in
80355-17	FO-103-S-880	880 μm	.035 in
80355-18	FO-103-S-1140	1140 μm	.045 in